

Dimension

Build to Order
Maximum -- 48" x 96" (4' x 8')

Acrylic Thickness

1/4"

Custom Etching

Custom Pitch and Depth Patterning
Across Acrylic - BYIBA Even Light System (c)

LED Intensity Options

Standard - 0.2W @ 1.00" spacing
CRI 80/48 Lumens Per Watt

High - 0.2W @ 0.50" spacing
CRI 80/48 Lumens Per Watt

Super - 0.50W @ 0.50" spacing
CRI 80/55 Lumens Per Watt
24V LED System

LED Color Options

3200 K / 5400 K / Custom

Extrusion

Aircraft Grade Aluminum
Colors
Standard - White/Black/Clear Anodized
Custom - Anodized Finishes/Full Powder Coat

Surround Extrusion

Aluminum "L" Extrusion -- Magnetically Holds Graphic

Face Material

Non-Glare Clear Acrylic

Frame Profiles

Single Side

Backer

White Reflective Metal Backer
White Reflective PVC Backer

Power Supplies

60W Power Adapter - UL Certified
100W Transformer Hard Wire - UL Certified

Installation Supports

Direct Wall Mount
Direct Wall Z-Clamp System
Aircraft Cable Hanging Systems
Custom

Wattage

Watts -- Based on LED Length / Intensity

Dimensions:

A) Depth

0.875" / 22.225mm

B) Frame Face

0.75" / 19.05mm

Applications:

Standard:

Indoor

Architectural Backlighting:

Retail Displays:

BYIBA Comerical Graphics

Signage:

